

	B. It.								
	Ratio								
MM W3450 DS	5.850, 5.476,							650 (871)
W34	4.913,< 4.583,		_	433 (581)	1		578 (775)		
Σ	4.077 L								
	250	300	350	400	450	500	550	600	65
								Р	ower (kV

Standard Equipment

- Oil cooler complete with fittings and flexible hoses.
- Integrated Brackets.
- Free Standing.
- Lube Oil Pump.

Model	W3450 DS								
Power/RPM (hp/RPM)	Maximum kW rated input (hp)	First ratio	Se	Maximum input RPM					
		4,077	4,462	4,615	4,846	2200			
		4,583	5,015	5,188	5,448				
0,361 (0,484)	794 (1065)	4,913	5,376	5,562	5,840				
		5,476	5,933	6,199	6,509				
		5,850	6,402	6,623	6,954				
Dry weight kg(lb)	1260 (2780)								
SAE bell	#0, #1								
Туре	Vertical offset	Vertical offset							
Kinematics	Non Reversible, Engine Wise and Counter Engine Wise								


Description


- A gearbox with two ratios.
- Can be used for very specific project with PTO and PTI.
- Robust design and easy onboard maintenance.
- Robust design also withstands continuous duty in workboat, dredger applications.
- Fully works tested, reliable and simple to install.
- Reverse reduction marine transmission with hydraulically actuated multi-disc clutches.
- Case hardened and precisely ground gear teeth for long life and smooth running.
- Robust cast iron casing for direct or remote mounting.
- Emergency "get home" capability.
- Design, manufacture and quality control standards comply with ISO.
- Suitable for twin installation with 100% rated power in ahead and astern condition.

Option


- Engine-matched torsional coupling.
- Propeller shaft flange and coupling bolt set.
- Classification by all major Classification Societies on request.
- PTO (live or clutchable).
- Electric trolling valve for slow-speed drive.
- Shaft brake.
- Electric clutch control.
- Trailing pump.







Model	Bell Housing SAE N °	А	В	С	H1	H2	НЗ	L1	L2	Dry Weight			
Model		Dimensions in mm								kg(lb)			
W3450 DS	#0, #1	379	804	484	390	746	0	839	90	1260 (2780)			



Output Coupling dimension											
,	Α		3	С				Bolt Holes			
								No.	Diameter (E)		
mm	inch	mm	inch	mm	inch	mm	inch	110.	mm	in	
320	12,6	270	10,6	175	6,89	43,5	1,69	10	27,5	1,08	

Masson Marine products are available all over the world through our network of dealers





