



		Sample Powers	kW (hp)
	Ratio		1178 (1579)
	5.633	785 (1053)	(1404)
	5.282		19 (1501)
	5.202	839 (1126)	1323 (1775)
	4.926	882 (1183)	1176 (1578)
8	4.506		1413 (1894)
W 7200	4.313	942 (1263)	1460 (1958
≥	4.313	973 (1305	5) 1298(1740) 1
	4.127	1036 (13	1382 (1853)
	3.949		1356 (1819)
	3.78, J	1017 (13	1564 (2097)
	3.296 ]	1042 (1	1398)
	(	200 400 600 800	1000 1200 1400 1600 Power (k
		1200 rpm 1600 rpm	

Model		W7200					
Power/RPM	kW/RPM (hp/RPM)	Maximum kW rated input (hp)		Ratio	Maximum input RPM		
0,869 (1	165)	1607 (2155)		3,296	1850		
0,009 (1	,105)	1007 (2155)		3,780	1030		
0,848 (1	,137)	1653 (2217)		3,949	1950		
0,864 (1	,158)	1727 (2316)		4,127	2000		
0,811 (1	,088)	1703 (2284)		4,313			
0,785 (1	,052)	1648 (2210)		4,506			
0,735 (0	,986)	1544 (2071)		4,926	2100		
0,700 (0	,938)	1469 (1970)		5,282			
0,654 (0	,877)	1374 (1843)		5,633			
Dry weight	kg(lb)	2000 (4410)					
SAE bell		#0, #00					
Туре		Vertical offse	et				
Kinematics		Reversible					

## Description

- Robust design and easy onboard maintenance.
- Robust design also withstands continuous duty in workboat, dredger applications.
- Fully works tested, reliable and simple to install.
- Reversing reduction marine transmission with hydraulically actuated multi-disc clutches.
- Case hardened and precisely ground gear teeth for long life and smooth running.
- Robust cast iron casing for direct or remote mounting.
- Emergency "get home" capability.
- Design, manufacture and quality control standards comply with ISO.
- Suitable for twin installation with 100% rated power in ahead and astern condition.


## **Standard Equipment**


- Oil cooler complete with fittings and flexible hoses.
- Integrated Brackets.
- Free Standing.
- Lube Oil Pump.

## Option


- Engine-matched torsional coupling.
- Propeller shaft flange and coupling bolt set.
- Classification by all major Classification Societies on request.
- PTO (live or clutchable).
- Electric trolling valve for slow-speed drive.
- Shaft brake.
- Electric clutch control.







	Bell Housing SAE N°	А	В	С	H1	H2	H3	L1	L2	Dry Weight
Model		Dimensions in mm								kg(lb)
W7200	#0, #00	400	848	470	315	908	25	807	130	2000 (4410)



<b>Output Coupling dimension</b>											
A	A		в С		D		Bolt Holes				
								No.	Diameter (E)		
mm	inch	mm	inch	mm	inch	mm	inch	NO.	mm	in	
390	15,4	336	13,2	250	9,8	40	1,6	10	31	1,2	

Masson Marine products are available all over the world through our network of dealers

Dealer:



contact@masson-marine.com 5 rue Henri Cavallier 89100 Saint Denis les Sens - France **Masson** 

f www.masson-marine.com in

